Basical

Specifications

Style Name	Basical SQ
Construction	Tufted Textured Loop Pile
Yarn System	BCF Synthetic Fiber
Dye Method	100% Solution Dyed
Gauge	1/10"
Production Weight	17 oz/yd²
Total Thickness	6.5 mm
Backing	FlexiBac
Tile Size	50 cm x 50 cm
Radiant Panel	ASTM E 648 Class 2
Smoke Density	ASTM E 662 Less than 450
Static Propensity	AATCC 134 Less than 3.5 kV
Colour Fastness to Light	AATCC 16E ≥4
Colour Fastness to Rubbing/Crocking	AATCC 165 ≥4
Dimensional Stability	AACHEN ≤0.2%
Foot Traffic Recommendation TARR	Light Commercial

Product specifications are indicative averages derived from sample testing and are subject to typical manufacturing tolerances and natural pattern variation. Details may change without notice.
For additional information on product characteristics, recycled content, or warranty coverage, please reach out to one of our representatives or refer to the contact information below.

Recommended Installation



Quarter turn



Brick Ashlar



Unilay



Vertical Ashlar

Contact

sales@smjf.com.sg
www.smjf.com.sg
+65 6261 1212

31 Jurong Port Road, South Wing
#02-20, Jurong Logistics Hub
Singapore 619115