


Hues Board




Specifications

Style Name	Hues Board SQ
Construction	Tufted Multi-Level Pattern Loop Pile
Yarn	100% Nylon 6
Dye Method	100% Solution Dyed
Gauge	1/12"
Total Thickness	6 mm ± 0.5 mm
Pile Weight	20 oz/yd ²
Backing	ComfortBac v2
Tile Size	50 cm x 50 cm
Packing	20 pcs = 5 m ² / ctn
Radiant Panel	ASTM E648 Class I
Smoke Density	ASTM E662 Less than 450
Static Propensity	AATCC 134 Less than 3.5 kV
Colour Fastness to Light	AATCC 16E ≥4
Colour Fastness to Rubbing/Crocking	AATCC 165 ≥4
Dimensional Stability	AACHEN ≤0.2%
Foot Traffic Recommendation TARR	Medium Commercial
Warranty	15 Years




Product specifications are indicative averages derived from sample testing and are subject to typical manufacturing tolerances and natural pattern variation. Details may change without notice. For additional information on product characteristics, recycled content, or warranty coverage, please reach out to one of our representatives or refer to the contact information below.

Recommended Installation




Quarter turn



Brick Ashlar



Unilay



Vertical Ashlar

Certifications



Credits contribution to:



Contact

sales@smjf.com.sg
www.smjf.com.sg
+65 6261 1212

31 Jurong Port Road, South Wing
#02-20, Jurong Logistics Hub
Singapore 619115