

LVT Series 4 Click




Specifications

Style Name	LVT Series 4 Click
Overall Gauge	5.0 mm
Wear Layer	0.5 mm
Surface Treatment	Antimicrobial Treatment
Tile Size - Stone	12" x 24" @ 10 pcs = 1.858 sm/box
Tile Size - Wood	7" x 48" @ 10 pcs = 2.17 sm/box
Fire Resistance	EN13501-1 Bfl-S1
Dimension stability	ISO 23999 \leq 0.25% / lineal ft (305 mm) - Pass
Curling After Exposure to Heat	ISO 23999 \leq 0.080" (2.0 mm) - Pass
Colour Fastness to Light	ISO105B02 Grade>6
Abrasion Resistance	EN660 Class T
Dynamic Coefficient of Friction	SS485 DCOF: 0.81 - Pass
Wear Classification	Commercial Grade Resilient Tile
Treatment	Anti-Bacterial with PUR™
Warranty	10 Years




Product specifications are indicative averages derived from sample testing and are subject to typical manufacturing tolerances and natural pattern variation. Details may change without notice. For additional information on product characteristics, recycled content, or warranty coverage, please reach out to one of our representatives or refer to the contact information below.


Recommended Installation




90°
Random



90°
Subway Style



45°
Random



45°
Subway Style

Certifications



Contact

sales@smjf.com.sg
www.smjf.com.sg
+65 6261 1212

31 Jurong Port Road, South Wing
#02-20, Jurong Logistics Hub
Singapore 619115