Wonder Weft

Specifications

Style Name	Wonder Weft Plank
Construction	Multi-Level Loop
Yarn	Universal Thrive® Matter Nylon 6
Dye Method	100% Solution Dyed
Stitches	8 per inch
Total Thickness	4.5-7.5 mm ±0.5mm
Pile Weight	25 oz/yd²
Backing	ComfortBac v2
Tile Size	25 cm x 100 cm
Packing	20 pcs = 5 m² / carton
Radiant Panel	ASTM E648 Class I
Smoke Density	ASTM E662 Less than 450
Static Propensity	AATCC 134 Less than 3.5 kV
Colour Fastness to Light	AATCC 16E ≥4
Colour Fastness to Rubbing/Crocking	AATCC 165 ≥4
Dimensional Stability	AACHEN ≤0.2%
Foot Traffic Recommendation TARR	Heavy Commercial
Warranty	15 Years



Product specifications are indicative averages derived from sample testing and are subject to typical manufacturing tolerances and natural pattern variation. Details may change without notice.
For additional information on product characteristics, recycled content, or warranty coverage, please reach out to one of our representatives or refer to the contact information below.

Recommended Installation



Ashlar



Herringbone



Basketweave

Certifications

Credits contribution to:

Contact

sales@smjf.com.sg
www.smjf.com.sg
+65 6261 1212

31 Jurong Port Road, South Wing
#02-20, Jurong Logistics Hub
Singapore 619115